

Tor Pluto



Model Number	Pluto 313	Pluto 411	Pluto 412	Pluto 714
Power Supply				
Supply Voltage	12-30 V DC	14-90 V DC	9-30 V DC	14-30 V DC
Max Supply Voltage	30 V DC	90 V DC	30 V DC	30 V DC
Reverse Polarity Protection	0 to -30 V DC	0 to -90 V DC	0 to -30 V DC	0 to -30 V DC
Max Operating Current	<100 mA	<100 mA	<100 mA	<100 mA
Peak Operating Current	2A @network activities	2A @network activities	2A @network activities	2A @network activities
BackUp Battery	NA	800 mAH , Li-Ion 3.7 V	800 mAH , Li-Ion 3.7 V	NA
Communication				
Cellular	4G- LTE-FDD B1/B3/B5/B8 LTE-TDD B34/B38/B39/ B40/B41	4G- LTE-FDD B1/B3/B5/B8 LTE-TDD B34/B38/B39/ B40/B41	4G- LTE-FDD B1/B3/B5/B8 LTE-TDD B34/B38/B39/ B40/B41	4G- LTE-FDD B1/B3/B5/B8 LTE-TDD B34/B38/B39/ B40/B41
	2G- GSM 900 MHz/1800 MHz	2G- GSM 900 MHz/1800 MHz	2G- GSM 900 MHz/1800 MHz	2G- GSM 900 MHz/1800 MHz
GNSS	GPS, GLONASS, BeiDou, Galileo, QZSS	GPS, GLONASS, BeiDou, Galileo, QZSS	GPS, GLONASS, BeiDou, Galileo, QZSS	
Network Protocol	TCP/IP, Mqtt	TCP/IP, Mqtt	TCP/IP, Mqtt	TCP/IP, Mqtt
Interfaces				
CAN	NA	1	1	NA
RS232/485	1 (RS485)	1 (RS485)	1 (RS232)	NA
Digital Input	NA	NA	4 (12-30 V)	2 (0-30 V)
Digital output	NA	NA	1 (1A, 60V)	1 (1A, 60V)
Analogue Input	NA	NA	2 (0-30 V)	2 (0-15V) single wire
Counter Input (0-1000 Hz)	NA	NA	NA	1
Hour Meter	NA	NA	NA	1
GNSS Antenna	External	Internal	External	Internal
Cellular Antenna	ExternalGSM	Internal GSM	External GSM	Internal GSM
SIM	Micro	Micro	Micro	Micro
Memory	1000 strings	64 MB	64 MB	64 MB
Bluetooth				
Specification	BLE 4.2	BLE 4.2	BLE 4.2	BLE 4.2
Additional Features				
Configuration / FOTA	Web configuration	Web configuration	Web configuration	Web configuration
Sensors	NA	NA	Accelerometer	NA
Physical Specification				
Dimension	104 * 91 * 36 (L*W*H)	104 * 91 * 36 (L*W*H)	104 * 91 * 36 (L*W*H)	104 * 91 * 36 (L*W*H)
Harness	4 Pin	4 Pin	16 Pin	8 Pin
Operating Environment				
Operating Temperature	-40 to +85 deg C	-40 to +85 deg C	-40 to +85 deg C	-40 to +85 deg C
Operating Humidity	85 Rh	85 Rh	85 Rh	85 Rh
Vibration	2g, 10-150 Hertz	2g, 10-150 Hertz	2g, 10-150 Hertz	2g, 10-150 Hertz
Enclosure Ingress Protection (IP)	IP 65	IP 65	IP 65	IP 67